



LPA3

.0.

0

LPA3 Portable Particle Counter

TAKE THE LAB WITH YOU WHEREVER YOU GO

PASSION TO PERFORM

MIS

LPA3

The world's most advanced mainstream portable particle counter

Whether you are working in the lab or in the field, MP Filtri's next-gen LPA3 delivers a fast, accurate and comprehensive hydraulic health check in a robust yet portable package.

Real-time monitoring and proactive maintenance safeguards machinery, enhances performance and productivity, and reduces costs and unplanned downtime

Featuring the latest breakthroughs in optical and photodiode technology, the new LPA3 enhances the reliability and longevity of complex hydraulic systems and is ideal for systems quality control in in-house manufacturing applications.

SIX REASONS LPA3 SETS NEW STANDARDS



ACCURACY

Using the latest LED optical technology, the LPA3 is accurate to $\pm 1/2$ code for 4, 6, 14µm(c).



MOBILITY

Highly durable and yet perfectly portable - weighing in at just 10kg (22lb).



ANALYSIS

Real-time monitoring and proactive maintenance.



SPEED

High-speed sample times over 16 times quicker than the LPA2.

EFFICIENCY

Slashes costs and downtime, protects machinery and rapidly pays for itself.



EASE OF USE

Sophisticated yet simple to use, the LPA3 can be mastered without formal training.

Robust and durable co-polymer body case

Greater storage capacity - store up to 4000 tests

Increased programmable sample volumes (up to 100 ml)

Instant results download via USB

Visit: www.mpfiltri.com / www.mpfiltri.co.uk

25/24/22

" The precision and extensive functionality of the LPA3 make it an essential tool, enabling us to eradicate even minute levels of contamination and give our customers an edge over the competition."

Wayne Hubball Technical Director, Reynolds Co



All the benefits of the laboratory in the field

The LPA3 is robust and light - weighing in at just 10kg, and it's ergonomic space-efficient design enables operators to work effectively in a wide variety of challenging work environments without having to make sacrifices to functionality.



Market-leading versatility

Not only is the LPA3 designed to thrive in a wide range of sectors and applications, the machine can also be personalised for peak performance with operators

able to tailor sample volumes and flush sizes; the amount of tests run concurrently; Capable of completing the 100ml sample test in just one minute.



Range of different connections

Easy-fit standard hydraulic connections maintain high environmental protection ratings. USB data connection enables rapid download of results to a data stick.

- A: M16 x 2 Test point connection
- B: Quick-release waste capture
- C: USB data stick download port
- D: PC-USB connection
- E: Power on/off with built in bi-colour LED
- F: IP rated DC charging port



Wide range of reporting formats

Wherever you are working and whatever standards you are using we've got you covered. We've also added five* new reporting standards.



Easy to use interface

Simple yet sophisticated software; highly responsive touchscreen with no need for a stylus; and a customisable home screen for all your key performance information at-a-glance.



Fast, smooth learning curve

Designed for ease of use, the LPA3 enables first time operators to get up and running in minutes - without the need for a dedicated training programme. The machine's sophisticated functionality sets new standards in the industry but is surprising easy to master, saving customers time and money.

LPA3 Specification



2

Technology	LED based light extinction automatic optical particle counter
Particle Sizing	>4, >6, >14, >21, >25, >38, >50, >70 μm(c)
Analysis Range	ISO 4406:2017 Code 8 to 24 NAS 1638 Class 2 to 12 AS4059/ISO11218 Rev E, Table 1 Size Codes 2-12 AS4059/ISO11218 Rev E, Table 2 Size Codes, A:000 to 12, B:00 to 12, C:00 to 12, D:2 to 12, AS4059 Rev F, Table 1 Size Codes 2-12 AS4059 Rev F, Table 2 Size Codes, cpc[000 to 12, 00 to 12, 00 to 12, 2 to 12, 4 to 12, 7 to 12] GBT14039 Code 8 to 24 GJB420B Size Codes, A:000 to 12, B:00 to 12, C:00 to 12, D:2 to 12, E: 4 to 12,F: 7 to 12
Accuracy	\pm 1/2 code for 4, 6, 14µm(c) \pm 1 code for larger sizes
Calibration	Individually calibrated with ISO Medium Test Dust (MTD) based on ISO 11171, on equipment certified by I.F.T.S. ISO 11943
Viscosity Range	Up to 400cSt
Fluid Temperature	Minimum: +5°C / +41°F Maximum: +80°C / +176°F
Ambient Temperature	Minimum: -10°C / +14°F Maximum: +80°C / +176°F
Pressure	Minimum: 2 bar / 29 PSI Maximum: 420 bar / 6091 PSI
Sample Volume	Maximum 100ml / 0.035 fl oz per pump stroke Test Volumes programmable by end user Pre-set volumes also available
Data Storage	Up to 4000 tests
Environmental Protection	IP 66 (Lid closed) IP54 (Lid open)
Power	Lithium-Ion rechargeable battery 18-19v 2.1-3.0A
Weight	10 kg / 22lbs
Product Dimensions	Width: 435mm / 17" Height: 292mm / 11" (not including handle) Depth: 155mm / 6"

FLEXIBILITY BUILT-IN AS STANDARD

The ultimate hydraulic health check for a wide range of different sectors

Fast, accurate and easy to use, the LPA3 quickly identifies the levels of contamination in your systems at the touch of a button.

Offering both real-time monitoring and predictive maintenance technology it is an essential tool for anyone serious about maximising the efficiency and performance of hydraulic systems.

Reduced downtime, lower operating costs and longer lifespans of machinery are just some of the benefits the LPA3 will deliver.



Mobile

Portable and precise, the LPA3 is ideal for applications where accuracy is vital even in challenging and variable working conditions.



Offshore

Capable of handling Aerospace Phosphate Ester, Mineral and Synthetic Oil, Subsea/ Offshore

water based fluids and more....



Industrial Keeps production lines working at full capacity – ensuring the best in performance and productivity.



Aviation

Minimises Aircraft on Ground downtime, dramatically reducing operational and maintenance costs.



Test Rigs

Delivers accurate and reliable comprehensive hydraulic health checks to a host of international standards.



Machine tools

Ideal for Precision Tooling, Injection Moulding, Presses and Power Packs - supports a wide range of industries.



Why choose MP Filtri as your partner for contamination control solutions?

MP Filtri prides itself on being the original and the best when it comes to portable particle counters.

The celebrated LPA2 set new standards in the industry at launch - and this new incarnation enhances and improves the original machine's market-leading functionality - delivering faster results, greater accuracy, more storage, extensive customisation options, and a more robust and portable design.

MP Filtri has a proud heritage spanning more than 50 years as an innovator in the hydraulic filtration industry and has forged a growing reputation for the quality of its products and its customer service.

When the vast majority of hydraulic failures are caused by contamination can you afford not to team up with MP Filtri and ensure your machinery is maximising its efficiency and potential?

Our Product Ranges

Portable Particle Counters

Innovative products to suit a variety of sectors and budgets from the CML 2.0 to the Airbus approved Aviation edition LPA2.



Bottle Samplers

A choice of 110ml and 500ml models, ideal for use in laboratories where fluid sampling at point of use is inaccessible or impractical.





In-line Contamination Monitors

Our market-leading ICM 2.0 and ICU models deliver the ultimate hydraulic health checks and are also Industry 4.0 ready.



Off-line Filtration Units

A comprehensive range of offline filling and filtration units to help service and maintenance teams deliver outstanding oil and hydraulic fluid cleanliness.

LPA 3 How to order

Order example		LPA3	W	Р	Μ	0	0	1
1. Contamination Monitoring Product								
LPA3= Light Extinction Particle Counter	_							
2. Sensor Options: Moisture								
0 = Without moisture and temperature sensor								
W = With moisture and temperature sensor	_							
	_							
3. Sensor Options: Pressure								
0 = Without on-screen inlet pressure display	_							
P = With on-screen inlet pressure display	_							
4 Eluid Composibility								
4. Fluid Compatibility								
M = Mineral Oil and Synthetic Fluids	_							
N = Subsea and water based fluids *	_							
S = Phosphate ester and aggressive fluids* **	_							
5. External Result Option								
0= Without on board printer								
1= With on board printer								
6. Design Reference								
0= Std option with full accessory kit and carry bag								
	-							
7. Country Plug Type								

1= UK,EU,US,AUS/CN

* N & S version, moisture sensor (W) not available ** S version not yet available

HEADQUARTERS

MP Filtri S.p.A. Via 1° Maggio, 3, 20060 Pessano con Bornago, Milano - Italy

BRANCH OFFICE

MP Filtri U.K. Ltd. Bourton Industrial Park Bourton on the Water GL54, 2HQ Gloucestershire

MP Filtri CANADA Inc. 8831 Keele Street Concord Ontari L4K 2N1 - Canada

MP Filtri GERMANY GmbH Hans-Wilhelmi-Straße 2 DE - 66386 St. Ingbert ITALFILTRI LLC

Russian Federation Yuryevskiy Pereulok 13 a, Building 1 111020 Moscow - Russia

MP Filtri FRANCE SAS Parc d'activités des Chanteraines 8 rue du Commandant d'Estienne d'Orves, Immeuble D3, 92390 Villeneuve la Garenne

MP Filtri USA Inc. 2055 Quaker Pointe Drive PA 18951 Quakertown



MP Filtri (Shanghai) Co., Ltd.

Room 501, Building 1, 555 Wanfang Road, Minhang District Shanghai - Pudong - 201204 China

MP Filtri India Pvt. Ltd.

Plot-7F, Raj Pinnacle, Brookefield Road, Whitefield 560048 Bangalore



PASSION TO PERFORM