

ICU

In-line Contamination Monitoring Unit





Contamination management

INDEX

| | Page |
|--|------|
| ① HYDRAULIC FLUIDS | 12 |
| ② FLUIDS CONTAMINATION | 12 |
| ③ EFFECTS OF CONTAMINATION ON HYDRAULIC COMPONENTS | 12 |
| ④ MEASURING THE SOLID CONTAMINATION LEVEL | 13 |
| ⑤ RECOMMENDED CONTAMINATION CLASSES | 16 |
| ⑥ WATER IN HYDRAULIC AND LUBRICATING FLUIDS | 16 |

1 HYDRAULIC FLUIDS

The fluid is the vector that transmits power, energy within an oleodynamic circuit. In addition to transmitting energy through the circuit, it also performs additional functions such as lubrication, protection and cooling of the surfaces.

The classification of fluids used in hydraulic systems is coded in many regulatory references, different Standards.

The most popular classification criterion divides them into the following families:

- MINERAL OILS

Commonly used oil deriving fluids.

- FIRE RESISTANT FLUIDS

Fluids with intrinsic characteristics of incombustibility or high flash point.

- SYNTHETIC FLUIDS

Modified chemical products to obtain specific optimized features.

- ECOLOGICAL FLUIDS

Synthetic or vegetable origin fluids with high biodegradability characteristics.

The choice of fluid for an hydraulic system must take into account several parameters.

These parameters can adversely affect the performance of an hydraulic system, causing delay in the controls, pump cavitation, excessive absorption, excessive temperature rise, efficiency reduction, increased drainage, wear, jam/block or air intake in the plant.

The main properties that characterize hydraulic fluids and affect their choice are:

- DYNAMIC VISCOSITY

It identifies the fluid's resistance to sliding due to the impact of the particles forming it.

- CINEMATIC VISCOSITY

It is a widespread formal dimension in the hydraulic field.

It is calculated with the ratio between the dynamic viscosity and the fluid density.

Cinematic viscosity varies with temperature and pressure variations.

- VISCOSITY INDEX

This value expresses the ability of a fluid to maintain viscosity when the temperature changes.

A high viscosity index indicates the fluid's ability to limit viscosity variations by varying the temperature.

- FILTERABILITY INDEX

It is the value that indicates the ability of a fluid to cross the filter materials. A low filterability index could cause premature clogging of the filter material.

- WORKING TEMPERATURE

Working temperature affects the fundamental characteristics of the fluid. As already seen, some fluid characteristics, such as cinematic viscosity, vary with the temperature variation.

When choosing a hydraulic oil, must therefore be taken into account of the environmental conditions in which the machine will operate.

- COMPRESSIBILITY MODULE

Every fluid subjected to a pressure contracts, increasing its density.

The compressibility module identifies the increase in pressure required to cause a corresponding increase in density.

- HYDROLYTIC STABILITY

It is the characteristic that prevents galvanic pairs that can cause wear in the plant/system.

- ANTIOXIDANT STABILITY AND WEAR PROTECTION

These features translate into the capacity of a hydraulic oil to avoid corrosion of metal elements inside the system.

- HEAT TRANSFER CAPACITY

It is the characteristic that indicates the capacity of hydraulic oil to exchange heat with the surfaces and then cool them.

2 FLUID CONTAMINATION

Whatever the nature and properties of fluids, they are inevitably subject to contamination. Fluid contamination can have two origins:

- INITIAL CONTAMINATION

Caused by the introduction of contaminated fluid into the circuit, or by incorrect storage, transport or transfer operations.

- PROGRESSIVE CONTAMINATION

Caused by factors related to the operation of the system, such as metal surface wear, sealing wear, oxidation or degradation of the fluid, the introduction of contaminants during maintenance, corrosion due to chemical or electrochemical action between fluid and components, cavitation. The contamination of hydraulic systems can be of different nature:

- SOLID CONTAMINATION

For example rust, slag, metal particles, fibers, rubber particles, paint particles or additives

- LIQUID CONTAMINATION

For example, the presence of water due to condensation or external infiltration or acids


- GASEOUS CONTAMINATION

For example, the presence of air due to inadequate oil level in the tank, drainage in suction ducts, incorrect sizing of tubes or tanks.

3 EFFECTS OF CONTAMINATION ON HYDRAULIC COMPONENTS

Solid contamination is recognized as the main cause of malfunction, failure and early degradation in hydraulic systems. It is impossible to delete it completely, but it can be effectively controlled by appropriate devices.

CONTAMINATION IN PRESENCE OF LARGE TOLERANCES




CONTAMINATION IN PRESENCE OF NARROW TOLERANCES



Solid contamination mainly causes surface damage and component wear.

- SURFACE EROSION
Cause of leakage through mechanical seals, reduction of system performance, variation in adjustment of control components, failures.
- ADHESION OF MOVING PARTS
Cause of failure due to lack of lubrication.
- DAMAGES DUE TO FATIGUE
Cause of breakdowns and components breakdown.

- MODIFICATION OF FLUID PROPERTIES
(COMPRESSIBILITY MODULE, DENSITY, VISCOSITY)
Cause of system's reduction of efficiency and of control.
It is easy to understand how a system without proper contamination management is subject to higher costs than a system that is provided.
- MAINTENANCE
Maintenance activities, spare parts, machine stop costs
- ENERGY AND EFFICIENCY
Efficiency and performance reduction due to friction, drainage, cavitation.



Liquid contamination mainly results in decay of lubrication performance and protection of fluid surfaces.

DISSOLVED WATER

- INCREASING FLUID ACIDITY
Cause of surface corrosion and premature fluid oxidation
- GALVANIC COUPLE AT HIGH TEMPERATURES
Cause of corrosion

FREE WATER - ADDITIONAL EFFECTS

- DECAY OF LUBRICANT PERFORMANCE
Cause of rust and sludge formation, metal corrosion and increased solid contamination
- BATTERY COLONY CREATION
Cause of worsening in the filterability feature
- ICE CREATION AT LOW TEMPERATURES
Cause damage to the surface
- ADDITIVE DEPLETION
Free water retains polar additives

Gaseous contamination mainly results in decay of system performance.

- CUSHION SUSPENSION
Cause of increased noise and cavitation.
- FLUID OXIDATION
Cause of corrosion acceleration of metal parts.


4 MEASURING THE SOLID CONTAMINATION LEVEL

The level of contamination of a system identifies the amount of contaminant contained in a fluid.

This parameter refers to a unit volume of fluid.

The level of contamination may be different at different points in the system. From the information in the previous paragraphs it is also apparent that the level of contamination is heavily influenced by the working conditions of the system, by its working years and by the environmental conditions.

What is the size of the contaminating particles that we must handle in our hydraulic circuit?




Contamination level analysis is significant only if performed with a uniform and repeatable method, conducted with standard test methods and suitably calibrated equipment.

To this end, ISO has issued a set of standards that allow tests to be conducted and express the measured values in the following ways.

- GRAVIMETRIC LEVEL - ISO 4405

The level of contamination is defined by checking the weight of particles collected by a laboratory membrane. The membrane must be cleaned, dried and desiccated, with fluid and conditions defined by the Standard.

The volume of fluid is filtered through the membrane by using a suitable suction system. The weight of the contaminant is determined by checking the weight of the membrane before and after the fluid filtration.



CONTAMINATION MANAGEMENT

- CUMULATIVE DISTRIBUTION OF THE PARTICLES SIZE - ISO 4406

The level of contamination is defined by counting the number of particles of certain dimensions per unit of volume of fluid. Measurement is performed by Automatic Particle Counters (APC).

Following the count, the contamination classes are determined, corresponding to the number of particles detected in the unit of fluid.

The most common classification methods follow ISO 4406 and SAE AS 4059 (Aerospace Sector) regulations.

NAS 1638 is still used although obsolete.

Classification example according to ISO 4406

The code refers to the number of particles of the same size or greater than 4, 6 or 14 μm in a 1 ml fluid.


| Class | Number of particles per ml | |
|-------|----------------------------|-----------|
| | Over | Up to |
| 28 | 1 300 000 | 2 500 000 |
| 27 | 640 000 | 1 300 000 |
| 26 | 320 000 | 640 000 |
| 25 | 160 000 | 320 000 |
| 24 | 80 000 | 160 000 |
| 23 | 40 000 | 80 000 |
| 22 | 20 000 | 40 000 |
| 21 | 10 000 | 20 000 |
| 20 | 5 000 | 10 000 |
| 19 | 2 500 | 5 000 |
| 18 | 1 300 | 2 500 |
| 17 | 640 | 1 300 |
| 16 | 320 | 640 |
| 15 | 160 | 320 |
| 14 | 80 | 160 |
| 13 | 40 | 80 |
| 12 | 20 | 40 |
| 11 | 10 | 20 |
| 10 | 5 | 10 |
| 9 | 2.5 | 5 |
| 8 | 1.3 | 2.5 |
| 7 | 0.64 | 1.3 |
| 6 | 0.32 | 0.64 |
| 5 | 0.16 | 0.32 |
| 4 | 0.08 | 0.16 |
| 3 | 0.04 | 0.08 |
| 2 | 0.02 | 0.04 |
| 1 | 0.01 | 0.02 |
| 0 | 0 | 0.01 |

> 4 $\mu\text{m}_{(c)}$ = 350 particles
 > 6 $\mu\text{m}_{(c)}$ = 100 particles
 > 14 $\mu\text{m}_{(c)}$ = 25 particles
 16 / 14 / 12

ISO 4406:2017 Cleanliness Code System

Microscope counting examines the particles differently to APCs and the code is given with two scale numbers only.

These are at 5 μm and 15 μm equivalent to the 6 $\mu\text{m}_{(c)}$ and 14 $\mu\text{m}_{(c)}$ of APCs.



- CUMULATIVE DISTRIBUTION OF THE PARTICLES SIZE - SAE AS 4059-1 and SAE AS 4059-2

Classification example according to SAE AS 4059-1 and SAE AS 4059-2

The code, prepared for the aerospace industry, is based on the size, quantity, and particle spacing in a 100 ml fluid sample. The contamination classes are defined by numeric codes, the size of the contaminant is identified by letters (A-F).

It can be made a differential measurement (Table 1) or a cumulative measurement (Table 2)

Table 1 - Class for differential measurement

| Class | Dimension of contaminant | | | | |
|-------|--------------------------|-------------------------|-------------------------|-------------------------|-----------------------|
| | 6÷14 µm _(c) | 14÷21 µm _(c) | 21÷38 µm _(c) | 38÷70 µm _(c) | >70 µm _(c) |
| 00 | 125 | 22 | 4 | 1 | 0 |
| 0 | 250 | 44 | 8 | 2 | 0 |
| 1 | 500 | 89 | 16 | 3 | 1 |
| 2 | 1 000 | 178 | 32 | 6 | 1 |
| 3 | 2 000 | 356 | 63 | 11 | 2 |
| 4 | 4 000 | 712 | 126 | 22 | 4 |
| 5 | 8 000 | 1 425 | 253 | 45 | 8 |
| 6 | 16 000 | 2 850 | 506 | 90 | 16 |
| 7 | 32 000 | 5 700 | 1 012 | 180 | 32 |
| 8 | 64 000 | 11 400 | 2 025 | 360 | 64 |
| 9 | 128 000 | 22 800 | 4 050 | 720 | 128 |
| 10 | 256 000 | 45 600 | 8 100 | 1 440 | 256 |
| 11 | 512 000 | 91 200 | 16 200 | 2 880 | 512 |
| 12 | 1 024 000 | 182 400 | 32 400 | 5 760 | 1 024 |

- 6÷14 µm_(c) = 15 000 particles
 - 14÷21 µm_(c) = 2 200 particles
 - 21÷38 µm_(c) = 200 particles
 - 38÷70 µm_(c) = 35 particles
 - > 70 µm_(c) = 3 particles
- Class 6

Table 2 - Class for cumulative measurement

| Class | Dimension of contaminant | | | | | |
|-------|---------------------------|---------------------------|----------------------------|----------------------------|----------------------------|----------------------------|
| | >4 µm _(c) A | >6 µm _(c) B | >14 µm _(c) C | >21 µm _(c) D | >38 µm _(c) E | >70 µm _(c) F |
| 000 | 195 | 76 | 14 | 3 | 1 | 0 |
| 00 | 390 | 152 | 27 | 5 | 1 | 0 |
| 0 | 780 | 304 | 54 | 10 | 2 | 0 |
| 1 | 1 560 | 609 | 109 | 20 | 4 | 1 |
| 2 | 3 120 | 1 217 | 217 | 39 | 7 | 1 |
| 3 | 6 250 | 2 432 | 432 | 76 | 13 | 2 |
| 4 | 12 500 | 4 864 | 864 | 152 | 26 | 4 |
| 5 | 25 000 | 9 731 | 1 731 | 306 | 53 | 8 |
| 6 | 50 000 | 19 462 | 3 462 | 612 | 106 | 16 |
| 7 | 100 000 | 38 924 | 6 924 | 1 224 | 212 | 32 |
| 8 | 200 000 | 77 849 | 13 849 | 2 449 | 424 | 64 |
| 9 | 400 000 | 155 698 | 27 698 | 4 898 | 848 | 128 |
| 10 | 800 000 | 311 396 | 55 396 | 9 796 | 1 696 | 256 |
| 11 | 1 600 000 | 622 792 | 110 792 | 19 592 | 3 392 | 512 |
| 12 | 3 200 000 | 1 245 584 | 221 584 | 39 184 | 6 784 | 1 024 |

- > 4 µm_(c) = 45 000 particles
 - > 6 µm_(c) = 15 000 particles
 - > 14 µm_(c) = 1 500 particles
 - > 21 µm_(c) = 250 particles
 - > 38 µm_(c) = 15 particles
 - > 70 µm_(c) = 3 particle
- Class from 2F to 4E

- CLASSES OF CONTAMINATION ACCORDING TO NAS 1638 (January 1964)

The NAS system was originally developed in 1964 to define contamination classes for the contamination contained within aircraft components.

The application of this standard was extended to industrial hydraulic systems simply because nothing else existed at the time.

The coding system defines the maximum numbers permitted of 100ml volume at various size intervals (differential counts) rather than using cumulative counts as in ISO 4406:1999. Although there is no guidance given in the standard on how to quote the levels, most industrial users quote a single code which is the highest recorded in all sizes and this convention is used on MP Filtri APC's.

The contamination classes are defined by a number (from 00 to 12) which indicates the maximum number of particles per 100 ml, counted on a differential basis, in a given size bracket.

Size Range Classes (in microns)

| Maximum Contamination Limits per 100 ml | | | | | |
|---|-----------|---------|--------|--------|-------|
| Class | 5÷15 | 15÷25 | 25÷50 | 50÷100 | >100 |
| 00 | 125 | 22 | 4 | 1 | 0 |
| 0 | 250 | 44 | 8 | 2 | 0 |
| 1 | 500 | 89 | 16 | 3 | 1 |
| 2 | 1 000 | 178 | 32 | 6 | 1 |
| 3 | 2 000 | 356 | 63 | 11 | 2 |
| 4 | 4 000 | 712 | 126 | 22 | 4 |
| 5 | 8 000 | 1 425 | 253 | 45 | 8 |
| 6 | 16 000 | 2 850 | 506 | 90 | 16 |
| 7 | 32 000 | 5 700 | 1 012 | 180 | 32 |
| 8 | 64 000 | 11 400 | 2 025 | 360 | 64 |
| 9 | 128 000 | 22 800 | 4 050 | 720 | 128 |
| 10 | 256 000 | 45 600 | 8 100 | 1 440 | 256 |
| 11 | 512 000 | 91 200 | 16 200 | 2 880 | 512 |
| 12 | 1 024 000 | 182 400 | 32 400 | 5 760 | 1 024 |

- 5÷15 µm_(c) = 42 000 particles
 - 15÷25 µm_(c) = 2 200 particles
 - 25÷50 µm_(c) = 150 particles
 - 50÷100 µm_(c) = 18 particles
 - > 100 µm_(c) = 3 particles
- Class NAS 8

- CUMULATIVE DISTRIBUTION OF THE PARTICLES SIZE - ISO 4407

The level of contamination is defined by counting the number of particles collected by a laboratory membrane per unit of fluid volume. The measurement is done by a microscope.

The membrane must be cleaned, dried and desiccated, with fluid and conditions defined by the Standard. The fluid volume is filtered through the membrane, using a suitable suction system.

The level of contamination is identified by dividing the membrane into a predefined number of areas and by counting the contaminant particles using a suitable laboratory microscope.

MICROSCOPE CONTROL AND MEASUREMENT



COMPARISON PHOTOGRAPHS

1 graduation = 10µm



| | | |
|---------------------|----------------|-------------------|
| ISO 4406:1999 | Class 16/14/11 | Class 22/20/17 |
| SAE AS4059E Table 1 | Class 5 | Class 11 |
| NAS 1638 | Class 5 | Class 11 |
| SAE AS4059E Table 2 | Class 6A/5B/5C | Class 12A/11B/11C |

- CLEANLINESS CODE COMPARISON

Although ISO 4406:2017 standard is being used extensively within the hydraulics industry other standards are occasionally required and a comparison may be requested. The table below gives a very general comparison but often no direct comparison is possible due to the different classes and sizes involved.

| ISO 4406:2017 | SAE AS4059 Table 2 | SAE AS4059 Table 1 | NAS 1638 |
|--|--|---|--|
| > 4 $\mu\text{m}_{(c)}$ 6 $\mu\text{m}_{(c)}$ 14 $\mu\text{m}_{(c)}$ | > 4 $\mu\text{m}_{(c)}$ 6 $\mu\text{m}_{(c)}$ 14 $\mu\text{m}_{(c)}$ | 4-6 6-14 14-21 21-38 38-70 >70 | 5-15 15-25 25-50 50-100 >100 |
| 23 / 21 / 18 | 13A / 12B / 12C | 12 | 12 |
| 22 / 20 / 17 | 12A / 11B / 11C | 11 | 11 |
| 21 / 19 / 16 | 11A / 10B / 10C | 10 | 10 |
| 20 / 18 / 15 | 10A / 9B / 9B | 9 | 9 |
| 19 / 17 / 14 | 9A / 8B / 8C | 8 | 8 |
| 18 / 16 / 13 | 8A / 7B / 7C | 7 | 7 |
| 17 / 15 / 12 | 7A / 6B / 6C | 6 | 6 |
| 16 / 14 / 11 | 6A / 5B / 5C | 5 | 5 |
| 15 / 13 / 10 | 5A / 4B / 4C | 4 | 4 |
| 14 / 12 / 09 | 4A / 3B / 3C | 3 | 3 |

5 RECOMMENDED CONTAMINATION CLASSES

Any are the nature and the properties of fluids, they are inevitably subject to contamination. The level of contamination can be managed by using special components called filters.

Hydraulic components builders, knowing the problem of contamination, recommend the filtration level appropriate to the use of their products.

Example of recommended contamination levels for pressures below 140 bar.

| | | | | | | |
|--|------------------------|------------------------|------------------------|-----------------------|-----------------------|-----------------------|
| Piston pumps with fixed flow rate | • | | | | | |
| Piston pumps with variable flow rate | | | • | | | |
| Vane pumps with fixed flow rate | | • | | | | |
| Vane pumps with variable flow | | | • | | | |
| Engines | • | | | | | |
| Hydraulic cylinders | • | | | | | |
| Actuators | | | | | • | |
| Test benches | | | | | | • |
| Check valve | • | | | | | |
| Directional valves | • | | | | | |
| Flow regulating valves | • | | | | | |
| Proportional valves | | | | • | | |
| Servo-valves | | | | | • | |
| Flat bearings | | | • | | | |
| Ball bearings | | | | • | | |
| ISO 4406 CODE | 20/18/15 | 19/17/14 | 18/16/13 | 17/15/12 | 16/14/11 | 15/13/10 |
| Recommended filtration $\beta_{x(c)} \geq 1.000$ | $\beta_{20(c)} > 1000$ | $\beta_{15(c)} > 1000$ | $\beta_{10(c)} > 1000$ | $\beta_{7(c)} > 1000$ | $\beta_{7(c)} > 1000$ | $\beta_{5(c)} > 1000$ |


6 WATER IN HYDRAULIC AND LUBRICATING FLUIDS

Water Content

In mineral oils and non aqueous resistant fluids water is undesirable. Mineral oil usually has a water content of 50-300 ppm (@40°C) which it can support without adverse consequences.

Once the water content exceeds about 300ppm the oil starts to appear hazy. Above this level there is a danger of free water accumulating in the system in areas of low flow. This can lead to corrosion and accelerated wear.

Similarly, fire resistant fluids have a natural water which may be different to mineral oil.



Saturation Levels

Since the effects of free (also emulsified) water is more harmful than those of dissolved water, water levels should remain well below the saturation point.


However, even water in solution can cause damage and therefore every reasonable effort should be made to keep saturation levels as low as possible. There is no such thing as too little water. As a guideline, we recommend maintaining saturation levels below 50% in all equipment.

TYPICAL WATER SATURATION LEVEL FOR NEW OILS

Examples:

Hydraulic oil @ 30°C = 200ppm = 100% saturation

Hydraulic oil @ 65°C = 500ppm = 100% saturation



W - Water and Temperature Sensing

"W" option, in MP Filtri Contamination Monitoring Products, indicates water content as a percentage of saturation and oil temperature in degrees centigrade. 100% RH corresponds to the point at which free water can exist in the fluid. i.e. the fluid is no longer able to hold the water in a dissolved solution.

The sensor can help provide early indication of costly failure due to free water, including but not exclusive to:

- Corrosion
- Metal surface fatigue e.g. bearing failure
- Reduced lubrication & load carrying characteristics

Different oils have different saturation levels and therefore RH (relative humidity) % is the best and most practical measurement.

Water absorber

Water is present everywhere, during storage, handling and servicing.

MP Filtri filter elements feature an absorbent media which protects hydraulic systems from both particulate and water contamination.

MP Filtri's filter element technology is available with inorganic microfiber media with a filtration rating 25 μm (therefore identified with media designation WA025, providing absolute filtration of solid particles to $\beta_{X(C)} = 1000$).

Absorbent media is made by water absorbent fibres which increase in size during the absorption process.

Free water is thus bonded to the filter media and completely removed from the system (it cannot even be squeezed out).

By removing water from your fluid power system, you can prevent such key problems as:

- corrosion (metal etching)
- loss of lubricant power
- accelerated abrasive wear in hydraulic components
- valve-locking
- bearing fatigue
- viscosity variance (reduction in lubricating properties)
- additive precipitation and oil oxidation
- increase in acidity level
- increased electrical conductivity (loss of dielectric strength)
- slow/weak response of control systems

Product availability - UFM Series:

- UFM 041
- UFM 051
- UFM 091
- UFM 181
- UFM 919

Filter Media




Fabric that absorbs water

Absorber media layer



The Filter Media has absorbed water



Description

Automatic Particle Counters

In-line Contamination Monitoring Unit

The ICU automatically measures particulate contamination levels in various hydraulic fluids and is designed for industrial applications.


It is designed to be manifold mounted directly to systems, where ongoing measurement or analysis is required, and where space and costs are limited.

> Features & Benefits

- Manifold mounting
- 3 channel contamination measurement
- Measures ISO 4406:2017
- Robust design and construction
- Pressure max. 350 bar
- Environmental protection IP65/67 versatile
- 4-20mA analogue output as standard

Scope of Supply

- 1 x ICU0M00G5P01
- 1 x Installation kit:
 - 4 x M6x1.0x60mm long fixing bolts
 - 2 x 6.50 ID x 1.5 CSD FKM o-ring seals
- 1 x Hard copy of calibration certificate



Right facing view



Front / Left facing view

Technical data

Technology

LED Based Light Extinction Automatic Optical Contamination Monitor

Particle Sizing

>4, 6, 14 $\mu\text{m}_{(c)}$ to ISO 4406:2017 Standard

Analysis range

ISO 4406:2017 Code 0 to 20

Accuracy

$\pm \frac{1}{2}$ code for 4,6,14 $\mu\text{m}_{(c)}$ across the analysis range

Calibration

Each unit individually calibrated with ISO Medium Test Dust (MTD) based on ISO 11171, on equipment certified by I.F.T.S. ISO 11943

Operating Flow Rate

200 ml/minute controlled by the built in flow control valve

Viscosity range

≤ 1000 cSt

Fluid temperature

From 0 °C to +80 °C

Ambient Temperature

From 0 °C to +60 °C

Pressure

Minimum: 50 bar

Maximum: 350 bar

Test time

Adjustable 10 - 3600 seconds

Communication options

4-20 mA time multiplex as standard

Environmental Protection

IP 65/67 versatile

Weight

1.4 Kg

Electrical Supply

24v DC +/- 20%


Power consumption

<2.2 W

Cable

Electrical cable has to be ordered separately (optional accessory), MP Filtri item no. 13.061000 - ICU Cable M12 4 pin 1.5m long.

Dimensions



AUTOMATIC PARTICLE COUNTER ICU

Configurations :

ICU 0 M 0 0 G5 P01

Without moisture sensor, Mineral oil, Without keypad/display, 4 to 20mA timed multiplex, Manifold mounted, Standard option

ICU 0 M 0 0 G5 Pxx

Customized version